

For Non-EU countries

Specs. Type	Model name	Photo	Frequency (MHz)	Required Amprifier	Sterilization methood	Connecting Dopplers						
						ES-100VX	ES-100V3	Bidop 7	Smartdop 45	Smartdop 30EX*2	DVM-4500	Smartdop XT
Vascular probe: Standard	BT*M05S8C* [†]		4/ 5/ 8/ 10	-	-	✓	✓	-	✓	✓	4/ 5/ 8	4/ 5/ 8
	BT*M05S8A* [†]											
	ST*M05S8C* [†]		4/ 5/ 8/ 10	-	-	-	-	✓	-	-	-	-
	ST*M05S8A* [†]											
2MHz probe: Standard	BT2M20S8C* [†]		2	-	-	✓	✓	-	✓	✓	-	-
	BT2M20S8A* [†]											
	ST2M25S8C* [†]		2	-	-	-	-	✓	-	-	-	-
	ST2M25S8A* [†]											
Vascular probe: Pencil	BP8M05S8A* [†]		8	-	-	✓	✓	-	✓	-	✓	✓
	SP8M05S8A* [†]		8	-	-	-	-	✓	-	-	-	-
Vascular probe: Flat monitoring	BF8M15S8A* [†]		8	-	-	✓	✓	-	✓	✓	✓	✓
	SF8M15S8A* [†]		8	-	-	-	-	✓	-	-	-	-
2MHz probe: Flat monitoring	BF2M20S8A* [†]		2	-	-	✓	✓	-	✓	-	-	-
Sterilizable probes												
Pencil	VRP-*		8/ 10/ 20	✓	Sterrad	✓	✓	✓	✓	-	8	-
Bayonet	NRP-*H		10/ 20	✓	Sterrad	✓	✓	✓	✓	-	-	-
Flexible	NRP-10HF NRP-20H1NF		10/ 20	✓	Sterrad	✓	✓	✓	✓	-	-	-
Flat monitoring	FDP-08		8	✓	Sterrad	✓	✓	✓	✓	-	✓	-
Pencil	ACP-08		8	✓	Autoclave (5 times)	✓	✓	✓	✓	-	✓	-
Long	LRP-*		8/ 10	✓	Sterrad	✓	✓	✓	✓	-	8	-
Curved	CRP-10H CRP-20H CRP-20H1N		10/ 20	✓	Sterrad	✓	✓	✓	✓	-	-	-
Bayonet, extra-thin	NP20M1S8A		20	-	Sterrad	-	-	-	-	-	✓	-
Flexible	NP10M2S8AF NP20M12S8AF		10/ 20	-	Sterrad	-	-	-	-	-	✓	-
Tucking	TK10M3S8AF TK10M4S8AF TK10M5S8AF		10	-	Sterrad	-	-	-	-	-	✓	-
Amplifier for PW probes	BDP*MS8		8/ 10/ 20	-	-	✓	✓	-	✓	-	8	-
	SBDP*MS8		8/ 10/ 20	-	-	-	-	✓	-	-	-	-
Other probes												
PPG probe	PG-21		-	-	-	-	✓	-	✓	✓	✓	-
	PG-30		-	-	-	-	-	✓	-	-	-	-
Foot temperature probe	TP-01		-	-	-	-	-	-	-	-	-	✓
	TP-02		-	-	-	-	✓	-	✓	-	-	-

*†: The last word “C” represents Curl type cable and “A” represents Straight type one.

*Frequency